



## **SITUATION**

A power tool manufacturer experienced warranty claims for a heavy duty service tool designed for skilled trades and contractors. Company engineers identified the root cause for the returns was fastener loosening.


## **LOCTITE SOLUTION**

The LOCTITE® Technical Sales Engineer reviewed the customer's situation and recommended LOCTITE® 277™ Threadlocker. It was selected for two reasons; it is easy to integrate into the tool assembly process and it is highly effective at preventing fastener loosening. During tool assembly a drop of LOCTITE® 277™ is applied to the fasteners. It's high viscosity keeps the liquid in the thread roots and prevents migration. Once the fastener is inserted and torqued the LOCTITE® 277™ liquid cures and converts to a tough shock and vibration resistance plastic threadlocker.

## **BENEFITS**

Integrating LOCTITE® 277™ into the tool assembly process resolved the fastener loosing warranty claims. This tool delivered the high reliability and high performance that skilled workers and contractors expect from this company's brand of professional power tools.

Product	Size	IDH
LOCTITE <sup>®</sup> 277™	50 ml	2596560
	250 ml	88449



All marks used are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere. ® = registered in the U.S. Patent and Trademark Office. © 2022 Henkel Corporation. All rights reserved. DSGN0023405 (12/22)







